

Towards a New Alternative to Assess the Validity of Driving Simulators: The Concept of Presence

Christophe Deniaud, Vincent Honnet, Benoit Jeanne
DRD/DRIA
PSA Peugeot Citroën
Vélizy-Villacoublay, France
christophe.deniaud@mpsa.com;
vincent.honnet@mpsa.com;
benoit.jeanne@mpsa.com

Daniel Mestre
CNRS, ISM, UMR 7287
Aix-Marseille University
Marseille, France
daniel.mestre@univ-amu.fr

Abstract— In this paper, we propose a new approach of the behavioral validity's assessment of driving simulators. Our ambition is to find a way of measuring "presence" to use it as a measure for ecological validity in driving simulators. The underlying assumption is that a person experiencing a strong sense of presence in the virtual environment will react in this environment as if it would be a real one. We propose to measure "presence" by measuring "attention" toward the driving task". Our objective is to demonstrate that the higher the subject's attention required by the primary driving task will be, the more the spatial presence will be felt. In the experiment, we tried to vary "attention" by adding a dual task and by adding traffic and measure driving performance and subjective "presence" (MEC-SPQ: Measurement, Effects, Conditions-Spatial Presence Questionnaire). The main result is a lack of congruence between subjective and behavioral measures.

Keywords-Simulation; Attention; Presence; Driving Simulator.

I. INTRODUCTION

In the 1960s, driving simulation was mainly used to train specific target audiences such as novice drivers, law enforcement officers and truck drivers [3]. Since then, many advances have been achieved in terms of computing, visual display and vehicle dynamics rendering [2]. Driving simulation was originally developed to avoid cost of field studies, allowing more control over circumstances and measurements, and ensuring safety in hazardous conditions [1]. In the second half of the twentieth century, simulation was being successfully applied to aeronautical, rail and maritime operations. In spite of significant differences, it is interesting to note that the development of driving simulation was based on the development of flight simulation. Driving is a dynamic task with a set of rapid control maneuvers involving critical feedback for avoiding obstacles and preventing crashes [10]. Compared to the activity performed by air line pilots, driving involves higher amplitude, and higher frequency cues. The motion feedback does not play a key role for the major part of slow maneuvers performed by civilian pilots. There is no evidence that motion base-simulators are more efficient than

fixed base simulators for training of commercial pilots [6]. Thus, there is a stark contrast between driving simulation and flight simulation (Civil aviation only). Compared to an airline pilot, a driver needs a higher degree of motion simulation. That is probably the reason why the use of flight simulators is more than commonplace for pilot training and, conversely driving simulators are not widely used for driver training due to the inherent higher complexity of the driving task.

Nowadays, driving simulators are usually designed for two purposes: research and training. The simulator is essentially used to place constraints on driver behavior in order to study driver distraction and workload or used as test beds for highway design [15]. The use of a modern advanced driving simulator for human factors research has many advantages such as experimental control, efficiency, expense, safety, and ease of data collection [20]. However, the literature describes some possible disadvantages, i.e., simulator sickness, accurate replication of physical sensations, and most importantly, validity.

In this paper, we will first look at a brief overview about the ecological validity to identify which specific issues still need to be addressed in driving simulation. Then a methodological alternative will be exposed through the concept of Presence. The remainder of the report basically consists of exposing results about this new experimental approach.

II. ECOLOGICAL VALIDITY

In spite of significant advancements in the physical fidelity of the driving simulation, a lack of realism seems to be always observed in the major part of driving simulator studies [4]. The most important question is to know in which extent measures from simulation are similar to those obtained in the real world. This multidimensional problem is called simulation validation [5]. This question has been a concern for at least 25 years. Blaauw [5] defined two types of validity. The first one is the absolute validity; it deals with the extent to which a manipulation of a variable in the real world produces the same or equivalent change in the same measure when manipulated in a driving simulator. The second one is called the relative validity and refers to the

extent to which the direction of change of a variable is in the same direction as a corresponding manipulation and measure in the real world [16]. If absolute validity is obviously desired by researchers, regarding the variability of driver performance, it seems highly unlikely to have an exact correspondence of on-road and simulation measures. Furthermore, there is no bad or good simulator from a methodological point of view. The simulation validation seems to be arbitrated between the research issue and how simulators are used to investigate this question.

Each simulator must be validated for a specific use. In addition, the question of simulation validation has followed the perpetual development of a significant number of simulator components as computers and various display technologies. That is the reason why, since four decades, simulators have been designed to deliver more and more perceptual cues to the driver in order to reproduce as accurately as possible the experience of driving an automobile. Thus, simulator validity is often addressed in the extent to which a physical variable in a simulator corresponds to its operationally equivalent component in the real world is called Physical fidelity [19]. As previously discussed, simulation validity is multidimensional and can be related to behavioral and physical dimensions [12], but also to the perceived sensation of the subjective experience and objective performance [30]. Indeed, despite significant advancements in the fidelity of the driving experience driving simulator studies continue to be criticized for lack of realism [9]. More specifically, the physical fidelity of the driving experience appears insufficient to overcome criticisms concerning the lack of psychological fidelity [8], defined as the extent to which the risks and rewards of participation in the experiment correspond to real-world risks and rewards [21]. The main problem is that driving experimental studies failed to provide a non-artificial trip purpose which could be able to reproduce drivers' motives inherent to the real driving activity.

Generally, it appears that the assessment of the validity of the virtual environment involves the comparison of results obtained from studies conducted in real situations and in virtual environment. However, this comparison is expensive (instrumentation) and complex (strict control of all the events occurring in a real situation). This is probably the reason why questions about the validity of simulators are most often pending [23] and why only few studies on this question can be found.

III. A METHODOLOGICAL ALTERNATIVE: THE CONCEPT OF PRESENCE

Driving simulation is a historical component of virtual reality, the purpose of which being to enable one person (or more) to develop sensori-motor and cognitive activity in an artificial world [17]. The interaction of a person with the virtual world is a transposition of the perception-cognition-

action loop of human behaviour in the real world. Immersion in a virtual world cannot be the same as in the real world [11], since the user has learned to act naturally in a real and physical world (without, for instance, any delay and/or sensorimotor bias). Thus, immersion, depending on the sensorimotor contingencies permitted by the simulator, is a necessary but not sufficient condition for the expression, within the virtual environment, of a performance that is representative of the actual situation [18]. Facing this problem, a concept emerged in the '80s from the early steps of research about virtual reality. This concept addresses the issue of "ecological" validity of the behaviour observed in virtual environments. It is the concept of presence. This multidimensional concept is considered as the ability of individuals to adopt behavioural patterns similar to that observed in everyday life and therefore as their propensity to respond to various stimuli by a realistic way [26].

Kaptein et al. [14] and Tichon [28] already proposed this concept as a tool for assessing driving or railway simulators but only in driving situations generating a state of stress. In studies about presence, finding a consensus about presence conceptualization in order to enhance its operationalization and its assessment [27] seems to be the main challenge. Various attempts have been made to describe this concept. Despite divergences, the major part of publications considers that presence rests on an attentional basis [22][24][25][31].

Thus, we decided to modulate experimentally the cognitive load induced during the simulated driving task, in order to generate different attentional states and finally to induce different levels of spatial presence. We crossed the two following independent variables: 1) A secondary task (dual-task paradigm), supposed to distract the driver from the primary task (driving) and 2) the presence of traffic on the roadway, supposed to focus the driver's attention toward the primary task. Our objective was to develop a sensitive measure of presence in order to assess the simulator validity. Our main hypotheses were:

-H1: The vehicle traffic in the virtual world is a positive predictor of the different sections of the MEC Spatial Presence Questionnaire.

-H2: A dual task performed during the driving is a negative predictor of the different sections of the MEC Spatial Presence Questionnaire and of the driving performance.

IV. METHOD

A. Participants

Twenty experienced car drivers, with at least five years of experience (14 men and 6 women), were divided into four groups, by crossing two independent variables, i.e., a dual task to be performed or not during the experiment and the presence or not of other vehicles' traffic on the road. The age of the participants ranged from 22 to 45 (M=32.8 years,

SD=6.45). All were tested on a voluntary basis, having signed an informed consent form.

B. Apparatus

The experiment was carried out using the SIM²-IFSTTAR (French Institute of Science and Technology for Transport) fixed-base driving simulator equipped with a multi-actor parallel architecture for traffic simulation (ArchiSim) and an object database SIM²-IFSTTAR (simulation software). The “ArchiSim” architecture was built on the DR2 traffic simulation model (management of “autonomous” and “enslaved” vehicle with a behavior defined by the scripts for each scenario, simulation generated by captors of punctual and space traffic) and on the 3D SIM2 loop of visualization [7]. The interactive driving station comprised one quarter of a vehicle including a seat, a dashboard, and controls equipped with captors, i.e. pedals and steering wheel. The projected display (at 30 Hz) presented a field of view of 150° horizontally and 40° vertically.

C. Procedure

In our experiment, we used a digital model of the Versailles Satory runway, which is a closed loop of 3.7km, with long straights and corners with different radii of curvature. The first factor was the level of attention induced by the virtual environment with two levels: automated bidirectional traffic or not. The second factor was the level of cognitive involvement induced by the real world with two levels: presence of a dual task or not. The secondary task consisted in launching every minute a digital hourglass by double clicking the mouse of a laptop positioned so that the person had to deport his gaze from the main visual scene. Half of the subjects had to perform the dual task, either in condition “traffic”, or in condition “no traffic” on the Satory circuit. The dual task might be considered as a derivative of the time-production task [33]. It is important to note that this dual task was used as a manipulation device and not as a performance measurement. That is the reason why reaction times were not presented in this paper. Whatever the experimental conditions, each participant had to perform 10 laps with a maximum speed of 110 km/h by respecting the Highway Code. We applied a 2 X 2 factorial design. Four experimental groups of five subjects were thus created (see Table I).

TABLE I. EXPERIMENTAL DESIGN

	Dual task	Traffic
Group1	No	Yes
Group2	Yes	Yes
Group3	No	No
Group4	Yes	No

D. MEC Spatial Presence Questionnaire

After each session, an adapted version of the MEC Spatial Presence Questionnaire (MEC-SPQ) [11][29] was used. As suggested for each scale, we used a 5-point Likert scale ranging from 1 (‘I do not agree at all’) to 5 (‘I fully agree’). We used 4-item scales for the tested dimensions. On the first level, Visual Spatial Imagery (VSI) was assessed with items such as “When someone describes a space to me, it’s usually very easy for me to imagine it clearly”; for allocation of attention “I dedicated myself completely to the medium”; for the Spatial Situational Model (SSM) “I was able to imagine the arrangement of the spaces presented in the medium very well”. On the second level, higher Cognitive Involvement (CogInv) was assessed with items such as “I thought most about things having to do with the medium”; for Suspension of Disbelief (Sod) “I didn’t really pay attention to the existence of errors or inconsistencies in the medium”. Finally, spatial presence was measured and analysed by the self-location dimension (e.g., «I felt as though I was physically present in the environment of the presentation”).

E. Driving performance

We analyzed two behavioral variables reflecting the driving performance, i.e. means and Standard Deviations of speed and of Lateral Position (SDLP).

V. RESULTS

A. MEC Spatial Presence Questionnaire

A mean score was computed for each group for the various dimensions of the MEC SPQ (see Table II). Overall, Whatever the section of the questionnaire, participants reported rather high scores. Specifically, “attention” scale (M= 4.2; SD=0.70) had the highest score while “cognitive involvement” scale (M=3.33; SD=0.95) had the lowest.

The generalized linear model was used in order to test our hypotheses, with a 2x2 factorial design and independent groups. Then multivariate analysis of variance (MANOVA) was considered for assessing interaction effects between independent variables. From the MANOVA analysis, no interaction effect was observed between the traffic condition and the dual task condition.

TABLE II. MEC SPQ RESULTS

	Group 1	Group 2	Group 3	Group 4
Attention	M=4.07 SD=0.72	M=4.27 SD=0.28	M=4.20 SD=0.93	M=4.33 SD=0.91
SSM	M=3.6 SD= 0.28	M=3.53 SD=0.73	M=4.27 SD=0.64	M=3.93 SD=0.60
CogInv	M=3.07 SD=1.19	M=3.80 SD=0.80	M=3.33 SD=1.10	M=3.13 SD=0.80
Sod	M=3.80 SD=0.65	M=3.67 SD=0.75	M=3.80 SD=0.90	M=3.93 SD=0.55
VSI	M=3.05 SD=0.74	M=3.85 SD=1.29	M=3.55 SD=0.51	M=4.30 SD=0.55
Self location	M=3.50 SD=0.71	M=4 SD=0.18	M=3.30 SD=1.31	M=3.7 SD=0.69

Whatever the experimental condition no significant effect was observed ($p < 0.05$) on the various sections of the MEC Spatial Presence Questionnaire. Contrary to what had been hoped the dual task and the traffic had no impact on the questionnaire results.

B. Driving performance

1) *Lateral Position*: An interaction effect was first observed between dual task and traffic ($F(1, 360) = 28.827; p < 0.01$). Lateral positions of Groups 1 and 2 submitted to traffic were higher than those of groups 3 and 4 not submitted to traffic (see Table III). A dual task effect is also observed in the absence of traffic, ($F(1, 360) = 35.27, p < 0.01$). Indeed, subjects not submitted to the dual task (Group3) had a higher mean lateral position compared to subjects submitted to the dual task (Group4).

TABLE III. LATERAL POSITION (M)

Groups	Means	SD
G1	1.42	0.80
G2	1.39	0.72
G3	0.98	0.99
G4	0.33	1.11

2) *Speed*: A dual task effect was observed ($F(9, 360) = 2.33; p = 0.012$) on 10 laps performed between groups not submitted to the dual task (group 1 and group 3) and groups submitted to the dual task (group 2 and group 4).

TABLE IV. SPEED (km/h)

Groups	Means	SD
G1 & G3	112.14	21.25
G2 & G4	103.02	23.99

Subjects not performing the dual task drove faster than others (see Table IV).

3) *SD of lateral position (SDLP)*: There was no interaction effect between group and lap variables ($F(24, 1754) = 0.60, p = 0.94$). However, the group significantly influenced the SDLP ($F(3, 1754) = 156.39, p < 0.01$). Over the 10 laps, the group 4 submitted to the dual task without traffic had the higher mean contrary to groups 1, 2, 3.

4) *SD of speed*: There was no interaction effect between group and lap variables ($F(24, 1754) = 0.60, p = 0.93$). However, the group significantly influenced the SD of speed ($F(3, 1754) = 41.018, p < 0.01$). Over the 10 laps, the group 2 submitted to the dual task with traffic had the higher mean contrary to groups 1, 3, 4.

V. DISCUSSION

Results globally showed that whatever the experimental condition, no significant difference was clearly observed for the different sections of our presence questionnaire. Indeed, the vehicle traffic in the virtual world was not a positive predictor of the different sections of the MEC Spatial Presence Questionnaire. The dual task was not a negative predictor of these different sections either. Although the dual task did not have a strong effect on the subjective measures of presence, it affected the behavioral measures. As described in the literature [13][32], low values in driving performance (SD of speed and SDLP) indicated a good steering control and a stable and consistent driving. Indeed, the SD of speed in traffic condition and the SDLP in no traffic condition were higher in dual task than in single task. Drivers submitted to the dual task without traffic drove in the middle of the road (the smallest mean lateral position), which could be interpreted as an efficient strategy but pretty inconsistent with the Highway Code. Similarly, participants submitted to the dual task in traffic condition have tried to reduce their speed as a compensatory strategy to deal with the dual task. Unfortunately, it appeared that they also failed to maintain a stable driving with a lack of speed control (the

highest SD of speed). Thus, driving performance seemed to be globally impaired by the dual task.

In conclusion, the main outcome was that behavioral measures revealed significant effects of the manipulated variables (traffic and dual task) on driving performance. These effects showed that participants took into account these variables. For instance, they indicate that traffic clearly influenced the lateral position in the lane, which can be considered as a positive (although rough) indicator of presence and reactivity to the simulator's scenario. However, these behavioral effects were not confirmed by subjective reports. One explanation could be that, whatever the current experimental conditions, driving activity did not involve high-level, conscious, cognitive processes. Despite high scores reported through the MEC Spatial Presence Questionnaire, driving was probably more based on a set of procedures or routines. Our experimental conditions might have been insufficient to induce several distinct levels of attention, involvement and suspension of disbelief, leading to several distinct levels of presence. Thus, high levels of self-reported presence (positively correlated with behavioral measures) might require to develop more challenging scenarios, in terms of controlled attention, cognitive involvement and more specifically, in terms of emotions induced by the media.

ACKNOWLEDGMENT

The authors would like to thank Thelma Coyle and Vincent Perrot for assistance in data entry and analysis.

REFERENCES

- [1] R. W. Allen and D. T. McRuer, The effect of adverse visibility on driver steering performance in an automobile simulator, SAE Transactions, Vol. 86, Feb. 1977, pp. 1081-1092.
- [2] R. W. Allen, A. C. Stein, B. L. Aponso, T. J. Rosenthal, and J. R. Hogue, A low cost, part task driving simulator based on microcomputer technology. Transportation Research Record, 1270, Sep. 1990, pp. 107-113.
- [3] R. W. Allen, and H. R. Jex, Driving simulation – Requirements, mechanization and application, SAE Technical Paper Series Paper number 800448, Feb. 1980, pp. 1-12.
- [4] R. W. Allen, D. G. Mitchell, A. C. Stein, and J. R. Hogue, Validation of real-time man-in-the-loop simulation. VTI Rapport, 372A, Part 4, Sep. 1991, pp. 18-31.
- [5] G. J. Blaauw, Driving experiments and task demands in simulator and instrumented car. Human Factors, Aug. 1982, pp. 473-486.
- [6] J. Bürki-Cohen and T. H. Go, The effect of simulator motion cues on initial training of airlines pilots. AIAA-2005-6109. Proceedings of the American Institute of Aeronautics and Astronautics Modeling and Simulation Technologies Conference. San Francisco, CA, Aug. 2005.
- [7] S. Espié, P. Gauriat, P. and M. Duraz, Driving simulators validation: The issue of transferability of results acquired on simulator. In National Advanced Driving Simulator, University of Iowa (Eds) Proc. Driving Simulation Conference DSC North-America'2005, november 30th - october 2nd, Orlando, FL., Center for Advanced Transportation Systems Simulation (2005), pp. 149-156.
- [8] S. T. Godley, T. J. Triggs, and B. N. Fildes, Driving simulator validation for speed research. Accident Analysis and Prevention, vol. 34, May. 2002, pp. 589–600.
- [9] M. Goodman, F. D. Bents, L. Tijerina, W. W. Wierwille, N. Lerner, and D. Benel, An investigation of the safety implications of wireless communications in vehicles (DOT HS 808 635). Washington, DC: National highway Traffic Safety Administration, US Department of Transportation, Jun 1997.
- [10] P. A. Hancock, The future of simulation. In D. Vicenzi, J. Wise, M. Mouloua, & P. A. Hancock (Eds.), Human factors in simulation and training Boca Raton, FL: CRC Press, Dec. 2008, pp. 169-188.
- [11] W. A. Ijsselsteijn, H. de Ridder, J. Freeman, and S. Avons, S. E. Presence: Concept, determinants and measurement. Paper presented at Photonics West-Human Vision and Electronic Imaging, San Jose, CA, Jan. 2000.
- [12] A. H. Jamson, Curve negotiation in the Leeds Driving Simulator: The role of driver experience. In D. Harris (Ed.), Engineering psychology and cognitive ergonomics. Ashgate, vol. 3, Dec. 1999, pp. 351-358.
- [13] S. L. Jamson and A. H. Jamson, The validity of a low-cost simulator for the assessment of the effects of in-vehicle information systems, SAFETY SCI, vol. 48, Aug. 2010, pp. 1477-1483.
- [14] M. J. Johnson, T. Chahal, A. Stinchcombe, N. Mullen, B. Weaver, and M. Bedard, Physiological responses to simulated and on-road driving. International Journal of Psychophysiology, vol. 81, Mar. 2011, pp. 203–208.
- [15] B. H. Kantowitz, Using microworlds to design intelligent interfaces that minimize driver distraction. Proceedings of the first international driving symposium on human factors in driver assessment, training and vehicle design, Aspen, CO, Aug. 2001, pp. 42-57.
- [16] N. A. Kaptein, J. Theeuwes, and R. Van der Horst, R, Driving simulator Validity: Some considerations. Transportation Research Record, 1550, Jan. 1996, pp. 30-36.
- [17] A. Kemeny and F. Panerai, Evaluating perception in driving simulation experiments, Trends in Cognitive Sciences, vol. 7, Jan. 2003, pp. 31–37.
- [18] K. M. Lee, Presence, explicated. Communication Theory, vol. 14, Jan. 2004, pp. 27–50.
- [19] A. T. Lee, Flight simulation. Aldershot, United Kingdom: Ashgate, 2005.
- [20] L. Nilsson, Behavioural research in an advanced driving simulator-experiences of the VTI system, Proceedings of the Human Factors and Ergonomics Society 37th Annual, Oct. 1993.
- [21] T. A. Ranney, L. A. Simmons, Z. Boulos, and M. M. Macchi, Effect of an afternoon nap on nighttime performance in a driving simulator, Transportation Research Record, 1686, Nov. 2000, pp. 49-56.
- [22] H. Regenbrecht and T. Schubert, Real and illusory interaction enhance presence in virtual environments.

- Presence: Teleoperators and Virtual Environments, 11, Aug. 2002, pp. 425-434.
- [23] B. Reimer, L. A. D'Ambrosio, J. E. Coughlin, M. E. Kafrisen, and J. Biederman, Using selfreported data to assess the validity of driving simulation data, *Behavior Research Methods*, vol. 38, Feb. 2006, pp. 314–324.
- [24] T. W. Schubert, A new conceptualization of spatial presence: Once again, with feeling. *Communication Theory*, vol. 19, May. 2009, pp. 161-187
- [25] T. W. Schubert, The sense of presence in virtual environments: A three-component scale measuring spatial presence, involvement, and realness. *Zeitschrift für Medienpsychologie*, vol. 15, Feb. 2003, pp. 69-71
- [26] M. Slater, B. Lotto, M. M. Arnold, and M. V. Sanchez-Vives, How we experience immersive virtual environments : the concept of presence and its measurement. *Anuario de Psicología*, vol. 40, Feb. 2009, pp. 193–210.
- [27] M. Slater, Measuring presence: A response to the Witmer and Singer presence questionnaire. *Presence: Teleoperators and Virtual Environments*, Vol. 8, Mar. 1999, pp. 560-565.
- [28] J. G. Tichon, Using presence to improve a virtual training environment. *CyberPsychology & Behavior*, vol. 10, Jun. 2007, pp. 781–787.
- [29] P. Vorderer, W. Wirth, F. R. F. Gouveia, T. Saari, F. Jäncke, S. Böcking, H. Schramm, A. Gysbers, T. Hartmann, C. Klimmt, J. Laarni, N. Ravaja, A. Sacau, T. Baumgartner, and P. Jäncke, MEC Spatial Presence Questionnaire (MEC-SPQ):Short Documentation and Instructions for Application. Report to the European Community, Project Presence : MEC (IST-2001-37661), Jun. 2004.
- [30] M. G. Wade and C. Hammond, Simulation validation: Evaluating driver performance in simulation and the real world. Final Report. (MN/RC-1998-28). Minneapolis, MN: University of Minnesota, Jul. 1998.
- [31] W. Wirth, T. Hartmann, S. Bocking, P. Vorderer, C. Klimmt, H. Schramm, T. Saari, J. Laarni, N. Ravaja, and F. R. Gouveia, A process model of the formation of spatial presence experiences. *Media Psychology*, vol. 9, Mar. 2007, pp. 493–525.
- [32] M. Wittmann, M. Kiss, P. Gugg, A. Steffen, M. Fink, E. Poppel, and H. Kamiya, Effects of display location of a visual in-vehicle task on simulated driving. *Appl.Ergon.* vol. 37, Nov. 2006, pp. 187–199.
- [33] D. Zakay, J. Shub, Concurrent duration production as a workload measure. *Ergonomics*, vol. 41, Aug. 1998, pp. 1115–1128.